CAISSON Stainless Steel Gauges

4" Model-47S-CAISSON

6" Model-67S-CAISSON

Self-contained gauges with sealed Bourdon tube; require no pipe connection. Designed to indicate the ambient pressure above any specified normal, usually the air surrounding the gauge above atmospheric, as in caisson work.



Case

AISI 316 Stainless Steel Bezel Stainless Steel (Bayonet type).

Socket + Element AISI 316 Stainless Steel

Movement Stainless Steel

Dial

White Aluminium (Black Printing) Fine scale markings Anti parallax mirror band

Pointer

Black Aluminium

Window Sheet Glass

Standard Size 100, 150mm

Accuracy class 1% of Full scale

Mounting types and Case types Supplied Rear Flange Panel Mount.

Scale Range

Range (FSW) Range (FSW)
0-70 0-500
0-140 0-700
0-230 0-1100
0-250 0-1200
0-300 0-1400
0-350 0-1700
0-450 0-2300



Model - 47S-Caisson

Other ranges available on request.

Optional extras

Monel to Nace MR-01-75 wetted parts. Laminated safety glass / Perspex window. Calibration certificates.

Further options: on request

How to order by Part Number

- 1 Model Number.
- 2 Choose Pressure Range.

| Model | Dial Range Code | Mounting Type | High Pressure Connection | 100% Glycerin Filled Recommended |
|-------------|-----------------------------|---------------|-----------------------------|-------------------------------------|
| 47S-CAISSON | 0-250 Feet Head Seawater | N/A | N/A | N/A |

Caisson Gauges


The Caisson Gauge is used inside the chamber and reads ambient chamber pressure. Accuracy is maintained for both increasing and decreasing pressures and always indicates true gauge pressure and/or a simulated depth in a chamber.

We manufacture a wide range of instruments to customer's special requirements We shall be pleased to discuss and advise on your specifications.

CAISSON Stainless Steel Gauges 4" Model-47S-CAISSON

6" Model-67S-CAISSON

Rear Flange Panel Mount



| | Α | В | С | D | Е | F |
|-------|------|------|------|------|------|------|
| 100mm | 132 | 51 | 99 | 121 | 6 | 118 |
| 4 in | 5.2 | 1.99 | 3.9 | 4.76 | 0.24 | 4.65 |
| 150mm | 196 | 51 | 148 | 184 | 5.8 | 178 |
| 6 in | 7.72 | 1.99 | 5.83 | 7.84 | 0.23 | 7.02 |

Warning: Before use please consult our recommendation regarding selection and installation. Copies available on request.

6786 Tipperary HOUSTON, TX 77061 USA Phone. 713-643-1022 713-643-2855 Fax. Toll Free. 1-800-901-1316 Web. stewartsusa.com